

Pump units



- Customizable to customer preferences
- Powerful pumps
- Many options available
- Smart Control

Sootsmid offers several pump units, designed with a strong focus on capacity, flexibility, and optimal ease of use for umbilical system slurry application. The pump unit is available in both trailed and mounted versions, with various sizes of buffer tanks. The units are compactly built and feature multiple connection options.

The slurry is pumped using a powerful PTO-driven centrifugal pump, and the flow rate can be accurately monitored via flow meters.

The exact configuration can largely be customized according to customer requirements, thanks to a wide range of options and features, such as remote control operation, a suction arm, a Sootsmid cutting filter, a generator set, or a platform with loading ramps, for example suitable for a quad or mini tractor.



Slootsmid Pump units

- Constant and reliable manure flow
 - High-capacity, powerful pump
 - Robust and durable construction
 - Easy to operate and maintain
 - Flexible integration into various systems
 - Designed for professional agricultural use
-



Stream 125

- BKT 800/65 R32 tyres
 - Tank consisting of a manure compartment of approx. 2.500 liters and a watercompartment of approx. 10.000 litres
 - 9.000 litre Börger-displacement pump
 - Doda AFI L35 HD-centrifugal pump
 - 8" suctionarm
 - ISOBUS-controlled system
-



Pump unit

- Three-point linkage
- 1.200 litre buffer tank
- Doda AFI L35 HD-centrifugal pump
- Hydraulic driven vacuum pump
- Water flow meter
- 8" cutting filter

